



SAFETY DATA SHEET

SDS No. C0513

Effective Date: 03/27/2019

1. IDENTIFICATION

(a) **Product identifier used on the label** CCEWOOL® POLYCRYSTALLINE WOOL FIBER BOARD

(b) **Other means of identification** Polycrystalline fiber, polycrystalline wool (PCW), man-made alumina fiber, high temperature insulation wool (HTIW)

(c) **Recommended use of the chemical and restrictions on use** PCW materials are used primarily in industrial high temperature insulating applications. Examples include heat shields, heat containment, gaskets, expansion joints, industrial furnaces, ovens, kilns, boilers and other process equipment and applications. PCW based products are not intended for direct sale to the general public. While PCWs are used in the manufacture of some consumer products, such as catalytic converter mats, the materials are contained, encapsulated, or bonded within the units.

(d) **Name, address, and telephone number**
DOUBLE EGRET THERMAL INSULATION CO.,LTD
Minying Industrial Park Development Zones Zibo,
Shandong, 255000
Tel: 0086 533 7986 860

2. HAZARDS IDENTIFICATION

(a) **Classification of the chemical**

In 1988 the International Agency for Research on Cancer (IARC) classified "ceramic fibers" as possible human carcinogens (Group 2B), and at that time, polycrystalline wool was included in this broad category of materials. See section 11 for more information.

The U.S. Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (HCS) 2012 indicates that IARC Group 2B corresponds to OSHA HCS 2012 Category 2 carcinogen classification (see, e.g., §1910.1200, Appendix F, Part D).

(b) Signal word, hazard statement(s), symbol(s) and precautionary statement(s)

Under OSHA HCS 2012 and WHMIS 2015, PCW is classified as a category 2 carcinogen.

Hazard Pictogram



Signal Word

Warning

Hazard Statements

Suspected of causing cancer by inhalation.

Precautionary statements

Do not handle until all safety instructions have been read and understood.
Use respiratory protection as required; see section 8 of the Safety Data Sheet.
If concerned about exposure, get medical advice.
Store in a manner to minimize airborne dust.
Dispose of waste in accordance with local, state and federal regulations.

Supplementary Information

May cause temporary mechanical irritation to exposed eyes, skin or respiratory tract.
Minimize exposure to airborne dust.

(c) Describe any hazards not otherwise classified that have been identified during the classification process

Mild mechanical irritation to skin, eyes and upper respiratory system may result from exposure.
These effects are usually temporary.

(d) Mixture rule

Not applicable.

3. COMPOSITION / INFORMATION ON INGREDIENTS

(a) Chemical and (b) Common Name

Refractories, Fibers, Aluminosilicate*

(c) CAS Number

675106-31-7*

% BY WEIGHT

100

*PCW can also be identified by a combination of CAS Numbers: 1344-28-1 (fibrous forms of Aluminium Oxide), 7631-86-9 (Silica, non-crystalline), or 1302-93-8 (Mullite).

4. FIRST AID MEASURES

- (a) **Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion**

SKIN

Handling of this material may generate mild mechanical temporary skin irritation. If this occurs, rinse affected areas with water and wash gently. Do not rub or scratch exposed skin.

EYES

In case of eye contact flush abundantly with water; have eye bath available. Do not rub eyes.

NOSE AND THROAT

If these become irritated move to a dust free area, drink water and blow nose. If symptoms persist, seek medical advice.

- (b) **Most important symptoms/effects, acute and delayed**

Mild mechanical irritation to skin, eyes and upper respiratory system may result from exposure. These effects are usually temporary.

- (c) **Indication of immediate medical attention and special treatment needed, if necessary**

NOTES TO PHYSICIANS

Skin and respiratory effects are the result of temporary, mild mechanical irritation; fiber exposure does not result in allergic manifestations.

5. FIRE FIGHTING MEASURES

- (a) **Suitable (and unsuitable) extinguishing media**

Use extinguishing agent suitable for surrounding combustible materials.

- (b) **Specific hazards arising from the chemical (e.g., nature of any hazardous combustion products):**

Non-combustible products, class of reaction to fire is zero. Packaging and surrounding materials may be combustible.

- (c) **Special protective equipment and precautions for fire-fighters**

NFPA Codes: Flammability: 0 Health: 1 Reactivity: 0 Special: 0

6. ACCIDENTAL RELEASE MEASURES

- (a) **Personal precautions, protective equipment, and emergency procedures**

Minimize airborne dust. Compressed air or dry sweeping should not be used for cleaning. See Section 8 "Exposure Controls / Personal Protection" for exposure guidelines.

- (b) **Methods and materials for containment and cleaning up**

Frequently clean the work area with vacuum or wet sweeping to minimize the accumulation of debris. Do not use compressed air for clean-up.

EMPTY CONTAINERS

Product packaging may contain residue. Do not reuse.

7. HANDLING AND STORAGE

(a) Precautions for safe handling

Handle fiber carefully to minimize airborne dust. Limit use of power tools unless in conjunction with local exhaust ventilation. Use hand tools whenever possible.

(b) Conditions for safe storage, including any incompatibilities

Store in a manner to minimize airborne dust.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

(a) OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limits used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available

<u>Components</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>MANUFACTURER</u>
Aluminosilicate fiber (polycrystalline)	Particulates Not Otherwise Regulated (PNOR) : Total Dust -- 15 mg/m ³ . Respirable Fraction -- 5 mg/m ³	Particulates Not Otherwise Classified (PNOC) : Inhalable particulate -- 10 mg/m ³ . Respirable particulate -- 3 mg/m ³	See below*

* As with most industrial materials, it is prudent to minimize unnecessary exposure to respirable dusts. Note that Industrial hygiene standards and occupational exposure limits differ between countries and local jurisdictions. Check with your employer to identify any "respirable dust", "total dust" or "fiber" exposure standards to follow in your area. If no regulatory dust or fiber control standard apply, a qualified industrial hygiene professional can assist with a specific evaluation of workplace conditions and the identification of appropriate respiratory protection practices. In the absence of other guidance, the supplier has found that it is generally feasible to control occupational fiber exposure to 0.5 f/cc or less.

The evaluation of occupational exposure limits and determining their relative applicability to the workplace is best performed, on a case-by-case basis, by a qualified Industrial Hygienist.

(b) Appropriate engineering controls

Use engineering controls such as local exhaust ventilation, point of generation dust collection, down draft work stations, emission controlling tool designs, and materials handling equipment designed to minimize airborne fiber emissions.

(c) Individual protection measures, such as personal protective equipment

Skin Protection

Wear personal protective equipment (e.g gloves), as necessary to prevent skin irritation. Washable or disposable clothing may be used. If possible, do not take unwashed clothing home. If soiled work clothing must be taken home, employees should be informed on best practices to minimize non-work dust exposure (e.g., vacuum

clothes before leaving the work area, wash work clothing separately, and rinse washer before washing other household clothes).

Eye Protection

As necessary, wear goggles or safety glasses with side shields.

Respiratory Protection

When engineering and/or administrative controls are insufficient to maintain workplace concentrations below the 0.5 f/cc REG or a regulatory OEL, the use of appropriate respiratory protection, pursuant to the requirements of OSHA Standards 29 CFR 1910.134 and 29 CFR 1926.103, is recommended. A NIOSH certified respirator with a filter efficiency of at least 95% should be used. The 95% filter efficiency recommendation is based on NIOSH respirator selection logic sequence for exposure to manmade mineral fibers. Pursuant to NIOSH recommendations, N-95 respirators are appropriate for exposures up to 10 times the NIOSH Recommended Exposure Limit (REL). With respect to RCF, both the NIOSH REL and the industry REG have been set at 0.5 fibers per cubic centimeter of air (f/cm³). Accordingly, N-95 would provide the necessary protection for exposures up to 5 f/cm³. Further, the Respirator Selection Guide published by 3M Corporation, the primary respirator manufacturer, specifically recommends use of N-95 respirators for RCF exposures. In cases where exposures are known to be above 5.0 f/cm³, 8 hour TWA, a filter efficiency of 100% should be used. Other factors to consider are the NIOSH filter series N, R or P -- (N) Not resistant to oil, (R) Resistant to oil and (P) oil Proof. These recommendations are not designed to limit informed choices, provided that respiratory protection decisions comply with 29 CFR 1910.134.

The evaluation of workplace hazards and the identification of appropriate respiratory protection is best performed, on a case by case basis, by a qualified Industrial Hygienist.

9. PHYSICAL AND CHEMICAL ROPERTIES

(a) Appearance	White, fibrous wool	(j) Upper/lower flammability or explosive limits	Not applicable
(b) Odor	Odorless	(k) Vapor pressure	Not applicable
(c) Odor threshold	Not applicable	(l) Vapor density	Not applicable
(d) pH	Not applicable	(m) Relative density	2.50 – 2.75
(e) Melting point	1760° C (3200° F)	(n) Solubility	Insoluble
(f) Initial boiling point and boiling range	Not applicable	(o) Partition coefficient: n-octanol/water	Not applicable
(g) Flash point	Not applicable	(p) Auto-ignition temperature	Not applicable
(h) Evaporation rate	Not applicable	(q) Decomposition temperature	Not applicable
(i) Flammability	Not applicable	(r) Viscosity	Not applicable

10. STABILITY AND REACTIVITY

- | | |
|-----------------------------------------------|----------------------------------------------------------|
| (a) Reactivity | PCW is non-reactive. |
| (b) Chemical stability | As supplied PCW is stable and inert. |
| (c) Possibility of hazardous reactions | None |
| (d) Conditions to avoid | Please refer to handling and storage advice in Section 7 |
| (e) Incompatible materials | None |
| (f) Hazardous decomposition products | None |

11. TOXICOLOGICAL INFORMATION

(a) through (d)

Toxicological Data/Epidemiology Data

Lifetime rat inhalation studies of polycrystalline fiber show that at the maximum dose level tested, there was no evidence of lung cancer, lung fibrosis or any other significant adverse effect. Intraperitoneal, intratracheal and intrapleural studies in rats, together with two in vitro tests, have all shown negative results. Despite some study limitations, it is important to note the consistent lack of carcinogenic response in animal studies.

As produced most polycrystalline fibers, including TEMPMAX® BOARD, have fiber diameters too large to be respirable. Numerous scientific studies suggest that the potential toxicity of a respirable fiber is directly related to bio-persistence (the length of time it takes for the fiber to clear the lung). Based on limited in-vitro laboratory analysis, which measure the dissolution rate of fibers in simulated lung fluid, polycrystalline fibers are known to be relatively durable.

Data from respiratory surveillance studies are not available for PCW workers. In a small cohort of workers exposed to PCW with historical co-exposures to RCF and other fibers, there was no evidence of interstitial lung disease on chest x-rays nor an accelerated rate of loss of lung function on pulmonary function testing. Symptom responses could not be attributed to or excluded from exposure to PCW as a consequence of the prior fiber exposures.

(e) International Agency for Research on Cancer and National Toxicology Program

In 1988, the International Agency for Research on Cancer (IARC) considered the carcinogenicity of several groups of fibers. One grouping they considered was a poorly defined collection of disparate fiber types [polycrystalline fiber, refractory ceramic fiber (referred to as RCF) and single crystal whiskers] into a broad, single category they termed "ceramic fibers". The IARC monograph clearly indicated that test data specific to polycrystalline fibers were negative, but according to the IARC classification principles, positive results with other fiber types led to the conclusion that all fibers in the group should be considered as possible human carcinogens (IARC Category 2B). In a subsequent monograph on MMVF (2002), IARC did not specifically re-evaluate polycrystalline fiber. The Annual Report on Carcinogens prepared by the National Toxicology Program (NTP), (latest edition) classified "ceramic fibers (respirable size)" as reasonably anticipated to be carcinogens.

12. ECOLOGICAL INFORMATION (Non-mandatory)

(a) Ecotoxicity (aquatic and terrestrial, where available)	No known aquatic toxicity.
(b) Persistence and degradability	These products are insoluble materials that remain stable over time and are chemically identical to inorganic compounds found in the soil and sediment; they remain inert in the natural environment.
(c) Bioaccumulative potential	No bioaccumulative potential.
(d) Mobility in soil	No mobility in soil.
(e) Other adverse effects (such as hazardous to the ozone layer)	No adverse effects of this material on the environment are anticipated.

13. DISPOSAL CONSIDERATIONS (Non-mandatory)

WASTE MANAGEMENT

To prevent waste materials from becoming airborne during waste storage, transportation and disposal, a covered container or plastic bagging is recommended.

DISPOSAL

This product, as manufactured, is not classified as a hazardous waste according to Federal regulations (40 CFR 261). Any processing, use, alteration or chemical additions to the product, as purchased, may alter the disposal requirements. Under Federal regulations, it is the waste generator's responsibility to properly characterize a waste material, to determine if it is a "hazardous" waste. Check local, regional, state or provincial regulations to identify all applicable disposal requirements.

14. TRANSPORT INFORMATION (Non-mandatory)

(a) UN number	Not Applicable
(b) UN proper shipping name	Not Applicable
(c) Transport hazard class(es)	Not Applicable
(d) Packing group, if applicable	Not Applicable
(e) Environmental hazards (e.g., Marine pollutant (Yes/No))	Not a marine pollutant
(f) Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)	Not Applicable
(g) Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises	Not Applicable

Canadian TDG Hazard Class & PIN: Not regulated

Not classified as dangerous goods under ADR (road), RID (train) or IMDG (ship).

15. REGULATORY INFORMATION (Non-mandatory)

UNITED STATES REGULATIONS

EPA	<p>Superfund Amendments and Reauthorization Act (SARA) Title III - this product does not contain any substances reportable under Sections 302, 304, 313, (40 CFR 372). Sections 311 and 312 (40 CFR 370) apply (delayed hazard).</p> <p>Toxic Substances Control Act (TSCA) - PCW has been assigned a CAS number; however, it is an "article" under TSCA and therefore exempt from listing on the TSCA inventory.</p> <p>Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) and the Clean Air Act (CAA) - this product contains fibers with an average diameter greater than one micron and thus is not considered a hazardous air pollutant.</p>
OSH	Comply with Hazard Communication Standards 29 CFR 1910.1200 and 29 CFR 1926.59 and the Respiratory Protection Standards 29 CFR 1910.134 and 29 CFR 1926.103.
California	"Ceramic fibers (airborne particles of respirable size)" is listed in Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986 as a chemical known to the State of California to cause cancer.
Other States	PCW products are not known to be regulated by states other than California; however, state and local OSHA and EPA regulations may apply to these products. If in doubt, contact your local regulatory agency.

INTERNATIONAL REGULATIONS

Canada **Canadian Environmental Protection Act (CEPA)** - All substances in this product are listed, as required, on the Domestic Substance List (DSL)

Europe The assessment of all available toxicological test data on polycrystalline fibers during the REACH registration process resulted in a "no classification" conclusion.

16. OTHER INFORMATION

Hazardous Materials Identification System (HMIS) Hazard Rating

HMIS Health	1* (* denotes potential for chronic effects)
HMIS Flammability	0
HMIS Reactivity	0
HMIS Personal Protective Equipment	X (To be determined by user)

DEFINITIONS

ACGIH:	American Conference of Governmental Industrial Hygienists
ADR:	Carriage of Dangerous Goods by Road (International Regulation)
CAA:	Clean Air Act
CAS:	Chemical Abstracts Service
CERCLA:	Comprehensive Environmental Response, Compensation and Liability Act
DSL:	Domestic Substances List
EPA:	Environmental Protection Agency
EU:	European Union
f/cc:	Fibers per cubic centimeter
HEPA:	High Efficiency Particulate Air
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association
IMDG:	International Maritime Dangerous Goods Code
mg/m³:	Milligrams per cubic meter of air
mmpcf:	Million particles per cubic meter
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
OSHA:	Occupational Safety and Health Administration
29 CFR 1910.134 & 1926.103:	OSHA Respiratory Protection Standards
29 CFR 1910.1200 & 1926.59:	OSHA Hazard Communication Standards
PEL:	Permissible Exposure Limit (OSHA)
PIN:	Product Identification Number
PNOC:	Particulates Not Otherwise Classified
PNOR:	Particulates Not Otherwise Regulated
RCRA:	Resource Conservation and Recovery Act
REL:	Recommended Exposure Limit (NIOSH)
RID:	Carriage of Dangerous Goods by Rail (International Regulations)
SARA:	Superfund Amendments and Reauthorization Act
SARA Title III:	Emergency Planning and Community Right to Know Act
SARA Section 302:	Extremely Hazardous Substances
SARA Section 304:	Emergency Release
SARA Section 311:	SDS/List of Chemicals and Hazardous Inventory
SARA Section 312:	Emergency and Hazardous Inventory
SARA Section 313:	Toxic Chemicals and Release Reporting
STEL:	Short Term Exposure Limit
SVF:	Synthetic Vitreous Fiber
TDG:	Transportation of Dangerous Goods
TLV:	Threshold Limit Value (ACGIH)
TSCA:	Toxic Substances Control Act
TWA:	Time Weighted Average
WHMIS:	Workplace Hazardous Materials Information System (Canada)

Revision Summary: Annual 2015 version.

DISCLAIMER

The information presented herein is presented in good faith and believed to be accurate as of the effective date of this Safety Data Sheet. Employers may use this SDS to supplement other information gathered by them in their efforts to assure the health and safety of their employees and the proper use of the product. This summary of the relevant data reflects professional judgment; employers should note that information perceived to be less relevant has not been included in this SDS. Therefore, given the summary nature of this document, LUYANG ENERGY-SAVING MATERIALS COMPANY LIMITED does not extend any warranty (expressed or implied), assume any responsibility, or make any representation regarding the completeness of this information or its suitability for the purposes envisioned by the user.