

CCEWOOL® Stone Wool Board 40



CCEWOOL® Stone Wool Board 40 is a high-performance stone wool insulation board designed for perimeter fire protection systems, floor and wall penetrations, construction joints, and other fire-related applications.

The product is non-combustible and fire-resistant, ensuring that even when exposed to flames, it will not produce toxic smoke or contribute to flame spread, providing reliable fire

protection for buildings. Additionally, its moisture resistance, anti-mold, and non-corrosive properties ensure long-lasting durability, while also reducing noise transmission within and around the building, significantly enhancing comfort in both residential and work environments.

CCEWOOL® Stone Wool Board 40 is the ideal solution for modern building fire and acoustic requirements, suitable for various key areas, providing comprehensive safety and thermal efficiency optimization for buildings.

Characteristics:

- Non-Combustible;
- Smoke and Flame Spread Resistance;
- Dimensional Stability;
- Low Thermal Conductivity;
- Water and Moisture Resistant;
- Corrosion and Mold Resistant.

Applications:

- Perimeter Fire Protection Systems;



Fire Insulation for Construction Joints;

Penetration Protection;

Other Fire Protection Applications.

TDS

CCEWOOL® Stone Wool Board 40	
Density	4.0 lbs/ft ³ (64 kg/m ³)
Dimensions	24" x 48" (610 mm x 1219 mm)
Thickness	1.5", 2", 3", 4", 5", 6" - 4" is available with a foil facing
Reaction to fire	Class A Non-Combustible
Reaction to moisture	Moisture Sorption - 0.04%
Corrosion Resistance	No corrosion

